

THICK BLEACH

Page: 1

Compilation date: 26/03/2023

Revision No: 1

# Section 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Product name: THICK BLEACH

Product Code: 112227

# 1.2. Relevant identified uses of the substance or mixture and uses advised against

# 1.3. Details of the supplier of the safety data sheet

Company name: Parc Supplies LTD

Vista House, Whitehall Point

Whitehall Road Leeds

LS12 4RZ

Tel: 0113 220 4080

Email: Info@parcglobal.com

# 1.4. Emergency telephone number

# Section 2: Hazards identification

#### 2.1. Classification of the substance or mixture

Classification under CHIP: Xi: R36/38; N: R50

Classification under CLP: Aquatic Acute 1: H400; Eye Dam. 1: H318; Skin Irrit. 2: H315; -: EUH031

Most important adverse effects: Irritating to eyes and skin. Very toxic to aquatic organisms.

# 2.2. Label elements

Label elements under CLP:

Hazard statements: EUH031: Contact with acids liberates toxic gas.

H315: Causes skin irritation.

H318: Causes serious eye damage.

H400: Very toxic to aquatic life.

Signal words: Danger

Hazard pictograms: GHS05: Corrosion

GHS09: Environmental





**Precautionary statements:** P264: Wash hands thoroughly after handling.

THICK BLEACH

Page: 2

P273: Avoid release to the environment.

P280: Wear protective gloves/protective clothing/eye protection/face protection.

P305+351+338: IF IN EYES: Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing.

P310: Immediately call a POISON CENTRE or doctor.

P332+313: If skin irritation occurs: Get medical advice/attention.

Label elements under CHIP:

Hazard symbols: Dangerous for the environment.

Irritant.





Risk phrases: R36/38: Irritating to eyes and skin.

R50: Very toxic to aquatic organisms.

Safety phrases: S61: Avoid release to the environment. Refer to special instructions / safety data sheets.

2.3. Other hazards

PBT: This product is not identified as a PBT/vPvB substance.

# Section 3: Composition/information on ingredients

# 3.2. Mixtures

## **Hazardous ingredients:**

# SODIUM HYPOCHLORITE SOLUTION CL ACTIVE

| EINECS    | CAS       | CHIP Classification    | CLP Classification                                    | Percent |
|-----------|-----------|------------------------|---|---------|
| 231-668-3 | 7681-52-9 | -: R31; C: R34; N: R50 | Skin Corr. 1B: H314; Aquatic Acute 1: H400; -: EUH031 | 1-10%   |

# SODIUM HYDROXIDE

| 215-185-5 | 1310-73-2 | C: R35 | Skin Corr. 1A: H314 | <1% |
|-----------|-----------|--------|---------------------|-----|
|-----------|-----------|--------|---------------------|-----|

# Section 4: First aid measures

# 4.1. Description of first aid measures

Skin contact: Remove all contaminated clothes and footwear immediately unless stuck to skin. Wash

immediately with plenty of soap and water.

**Eye contact:** Bathe the eye with running water for 15 minutes. Consult a doctor.

Ingestion: Wash out mouth with water. Consult a doctor.

Inhalation: Remove casualty from exposure ensuring one's own safety whilst doing so. Consult a

doctor.

# 4.2. Most important symptoms and effects, both acute and delayed

**Skin contact:** There may be irritation and redness at the site of contact.

THICK BLEACH

Page: 3

**Eye contact:** There may be irritation and redness. The eyes may water profusely.

Ingestion: There may be soreness and redness of the mouth and throat.

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest. Exposure may

cause coughing or wheezing.

**Delayed** / **immediate effects:** Immediate effects can be expected after short-term exposure.

#### 4.3. Indication of any immediate medical attention and special treatment needed

Immediate / special treatment: Eye bathing equipment should be available on the premises.

# Section 5: Fire-fighting measures

## 5.1. Extinguishing media

Extinguishing media: Suitable extinguishing media for the surrounding fire should be used. Use water spray

to cool containers.

#### 5.2. Special hazards arising from the substance or mixture

**Exposure hazards:** In combustion emits toxic fumes.

# 5.3. Advice for fire-fighters

Advice for fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact

with skin and eyes.

#### Section 6: Accidental release measures

# 6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: Refer to section 8 of SDS for personal protection details. If outside do not approach from

downwind. If outside keep bystanders upwind and away from danger point. Mark out the

contaminated area with signs and prevent access to unauthorised personnel. Turn

leaking containers leak-side up to prevent the escape of liquid.

# 6.2. Environmental precautions

Environmental precautions: Do not discharge into drains or rivers. Contain the spillage using bunding.

# 6.3. Methods and material for containment and cleaning up

Clean-up procedures: Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for

disposal by an appropriate method.

## 6.4. Reference to other sections

Reference to other sections: Refer to section 8 of SDS.

# Section 7: Handling and storage

#### 7.1. Precautions for safe handling

Handling requirements: Avoid direct contact with the substance. Ensure there is sufficient ventilation of the area.

Do not handle in a confined space. Avoid the formation or spread of mists in the air.

THICK BLEACH

Page: 4

# 7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Store in cool, well ventilated area. Keep container tightly closed. The floor of the storage

room must be impermeable to prevent the escape of liquids.

#### 7.3. Specific end use(s)

Specific end use(s): No data available.

# Section 8: Exposure controls/personal protection

#### 8.1. Control parameters

# **Hazardous ingredients:**

# SODIUM HYDROXIDE

#### Workplace exposure limits:

#### Respirable dust

| State | 8 hour TWA | 15 min. STEL | 8 hour TWA | 15 min. STEL |
|-------|------------|--------------|------------|--------------|
| UK    | -          | 2 mg/m3      | -          | -            |

#### **DNEL/PNEC Values**

**DNEL / PNEC** No data available.

## 8.2. Exposure controls

Engineering measures: Ensure there is sufficient ventilation of the area. The floor of the storage room must be

impermeable to prevent the escape of liquids.

Respiratory protection: Self-contained breathing apparatus must be available in case of emergency.

Hand protection: Protective gloves.

Eye protection: Safety glasses. Ensure eye bath is to hand.

Skin protection: Protective clothing.

# Section 9: Physical and chemical properties

# 9.1. Information on basic physical and chemical properties

State: Liquid

Colour: Off-white

Odour: Characteristic odour

Evaporation rate: Slow

Solubility in water: Miscible in all proportions

Viscosity: Viscous

Boiling point/range ℃: >35 Flash point ℃: >93

# 9.2. Other information

Other information: No data available.

THICK BLEACH

Page: 5

# Section 10: Stability and reactivity

#### 10.1. Reactivity

Reactivity: Stable under recommended transport or storage conditions.

#### 10.2. Chemical stability

Chemical stability: Stable under normal conditions.

#### 10.3. Possibility of hazardous reactions

Hazardous reactions: Hazardous reactions will not occur under normal transport or storage conditions.

Decomposition may occur on exposure to conditions or materials listed below.

#### 10.4. Conditions to avoid

Conditions to avoid: Heat.

#### 10.5. Incompatible materials

Materials to avoid: Strong oxidising agents. Strong acids.

#### 10.6. Hazardous decomposition products

Haz. decomp. products: In combustion emits toxic fumes.

# **Section 11: Toxicological information**

# 11.1. Information on toxicological effects

#### **Hazardous ingredients:**

# SODIUM HYPOCHLORITE SOLUTION...100% CL ACTIVE

| ORL MUS | LD50 | 5800 mg/kg |  |
|---------|------|------------|--|
|---------|------|------------|--|

#### **SODIUM HYDROXIDE**

| IPR | MUS | LD50 | 40  | mg/kg |
|-----|-----|------|-----|-------|
| ORL | RBT | LDLO | 500 | mg/kg |

## Relevant effects for mixture:

| Effect     | Route   | Basis                 |
|------------|---------|-----------------------|
| Irritation | OPT DRM | Hazardous: calculated |

# Symptoms / routes of exposure

**Skin contact:** There may be irritation and redness at the site of contact.

Eye contact: There may be irritation and redness. The eyes may water profusely.

**Ingestion:** There may be soreness and redness of the mouth and throat.

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest. Exposure may

cause coughing or wheezing.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

THICK BLEACH

Page: 6

# **Section 12: Ecological information**

12.1. Toxicity

Ecotoxicity values: No data available.

12.2. Persistence and degradability

Persistence and degradability: Not biodegradable.

12.3. Bioaccumulative potential

Bioaccumulative potential: Bioaccumulation potential.

12.4. Mobility in soil

Mobility: Readily absorbed into soil.

12.5. Results of PBT and vPvB assessment

PBT identification: This product is not identified as a PBT/vPvB substance.

12.6. Other adverse effects

Other adverse effects: Toxic to aquatic organisms. Toxic to soil organisms.

#### Section 13: Disposal considerations

# 13.1. Waste treatment methods

Disposal operations: Transfer to a suitable container and arrange for collection by specialised disposal

company.

NB: The user's attention is drawn to the possible existence of regional or national

regulations regarding disposal.

# **Section 14: Transport information**

14.1. UN number

UN number: UN3082

14.2. UN proper shipping name

Shipping name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.

14.3. Transport hazard class(es)

Transport class: 9

14.4. Packing group

Packing group: |||

14.5. Environmental hazards

Environmentally hazardous: Yes Marine pollutant: No

14.6. Special precautions for user

Special precautions: No special precautions.

Tunnel code: E

THICK BLEACH

Page: 7

Transport category: 3

# Section 15: Regulatory information

## 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### 15.2. Chemical Safety Assessment

#### Section 16: Other information

#### Other information

Other information: This safety data sheet is prepared in accordance with Commission Regulation (EU) No

453/2010.

\* indicates text in the SDS which has changed since the last revision.

Phrases used in s.2 and s.3: EUH031: Contact with acids liberates toxic gas.

H314: Causes severe skin burns and eye damage.

H315: Causes skin irritation.

H318: Causes serious eye damage.

H400: Very toxic to aquatic life.

R31: Contact with acids liberates toxic gas.

R34: Causes burns.

R35: Causes severe burns.

R36/38: Irritating to eyes and skin.

R50: Very toxic to aquatic organisms.

**Legend to abbreviations:** PNEC = predicted no effect concentration

DNEL = derived no effect level

LD50 = median lethal dose

LC50 = median lethal concentration

EC50 = median effective concentration

IC50 = median inhibitory concentration

dw = dry weight

bw = body weight

cc = closed cup

oc = open cup

MUS = mouse

GPG = guinea pig

RBT = rabbit

HAM = hamster

HMN = human

MAM = mammal

PGN = pigeon

IVN = intravenous

# THICK BLEACH

SCU = subcutaneous

SKN = skin

DRM = dermal

OCC = ocular/corneal

OPT = optical

INH = inhalation

PCP = phycico-chemical properties

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive

and shall be used only as a guide. This company shall not be held liable for any

damage resulting from handling or from contact with the above product.

Page: 8